

PROBLEM

NEC 250.70 Methods of Grounding and Bonding Conductor Connection To Electrodes.
Ground clamps shall be listed for the materials of the grounding electrode...

SOLVED



The problem is most acorn clamps are **NOT listed** for galvanized or stainless steel ground rods. If one of those clamps is installed on an electrode for which it is not listed, the installation does not meet code. Galvan has the solution.

New Galvan G-5 and SRC grounding clamps are **UL listed** and made in the USA. They are listed for copper coated, galvanized and stainless steel ground rods. They are also listed for rebar (UFER) grounds. How do you know? Because it's stamped right in the casting. Galvan has the clamps that make grounding code compliant. That's one less problem for you.

Galvan Industries, Inc.
www.galvanelectrical.com • 704-455-5102




Made in USA

NEC 250.70 Compliant Grounding Clamps

G-5 GROUND ROD CLAMP




- UL listed for copper-coated, galvanized and stainless steel ground rods
- UL listed for #4 rebar
- UL listed for direct burial in earth and concrete with a stainless steel bolt
- Cast copper alloy body with hex head bolt provides simple trouble-free connection at low cost.
- Able to withstand torque in excess of UL 467 requirements of 150 in/lb
- **Made in USA** 

Galvan G-5	Ground Rod Size, Inches	Rebar Size	Wire Range - AWG No. (CU)	Barcode
UL Listed, Direct Burial, Carton quantity: 50	1/2 (0.500) to 5/8 (0.625) For Copper Coated, Galvanized and Stainless Steel	#4 (1/2 inch)	10 AWG - 2 AWG	632591-70708-4
	5/8 UL Galvanized (0.539 to 0.555)		10 AWG - 2 AWG	
	5/8 F Full Size Galvanized (0.625 - 0.640)		10 AWG Solid - 2 AWG Solid, 10 AWG Stranded - 3 AWG Stranded	

SRC Universal Ground Rod Clamp



- UL listed for copper coated, galvanized, and stainless steel ground rods
- UL listed for #4, #5 and #6 rebar
- UL listed for direct burial in earth and concrete with a stainless steel bolt
- Performs the functions of economy, standard duty, heavy duty, and extra heavy duty
- Able to withstand torque in excess of UL 467 requirements of 150 in/lb
- RUS listed
- **Made in USA** 

Galvan SRC	Ground Rod Size, Inches	Rebar Size	Wire Range - AWG No. (CU)	Barcode
Direct Burial, Carton Quantity: 50	1/2 (0.500) to 3/4 (0.75) For Copper Coated, Galvanized and Stainless Steel	#5 (5/8 inch) , #6 (3/4 inch)	10 AWG - 1/0	632591-61344-6
	3/4 F (0.750 - 0.765) Full Size Galvanized	#4 (1/2 inch)	10 AWG Solid - 2 AWG Solid, 8 AWG Stranded - 1 AWG Stranded	

