

# PROBLEM

NEC 250.70 Methods of Grounding and Bonding Conductor Connection To Electrodes.  
**Ground clamps shall be listed for the materials of the grounding electrode...**

# SOLVED



The problem is some acorn clamps are **NOT** specifically listed for each type of grounding electrode. If a clamp is installed on an electrode for which it is not listed, the installation does not meet code. Galvan has the solution.

**New US-made Galvan G-5 and SRC ground clamps are UL listed for copper-bonded, galvanized and stainless steel ground rods. They are also listed for rebar (UFER) grounds.** How do you know? Because it's stamped right in the casting. Galvan has the clamps that make grounding code compliant. That's one less problem for you.

**Galvan Industries, Inc.**  
www.galvanelectrical.com • 704-455-5102




Made in USA



# NEC 250.70 Compliant Grounding Clamps

## G-5 GROUND ROD CLAMP




- UL listed for copper-coated, galvanized and stainless steel ground rods
- UL listed for #4 rebar
- UL listed for direct burial in earth and concrete with a stainless steel bolt
- Cast copper alloy body with hex head bolt provides simple trouble-free connection at low cost.
- Able to withstand torque in excess of UL 467 requirements of 150 in/lb
- **Made in USA** 

Galvan G-5	Ground Rod Size, Inches	Rebar Size	Wire Range - AWG No. (CU)	UPC #
UL Listed, Direct Burial, Carton quantity: 50	1/2 (0.500) to 5/8 (0.625) For Copper Coated, Galvanized and Stainless Steel	#4 (1/2 inch)	10 AWG - 2 AWG	632591-70708-4
	5/8 UL Galvanized (0.539 to 0.555)		10 AWG - 2 AWG	
	5/8 F Full Size Galvanized (0.625 - 0.640)		10 AWG Solid - 2 AWG Solid, 10 AWG Stranded - 3 AWG Stranded	

## SRC Universal Ground Rod Clamp



- UL listed for copper coated, galvanized, and stainless steel ground rods
- UL listed for #4, #5 and #6 rebar
- UL listed for direct burial in earth and concrete with a stainless steel bolt
- Performs the functions of economy, standard duty, heavy duty, and extra heavy duty
- Able to withstand torque in excess of UL 467 requirements of 150 in/lb
- RUS listed
- **Made in USA** 

Galvan SRC	Ground Rod Size, Inches	Rebar Size	Wire Range - AWG No. (CU)	UPC #
Direct Burial, Carton Quantity 50	1/2 (0.500) to 3/4 (0.75) For Copper Coated, Galvanized and Stainless Steel	#5 (5/8 inch) , #6 (3/4 inch)	10 AWG - 1/0	632591-61328-6
	3/4 F (0.750 - 0.765) Full Size Galvanized	#4 (1/2 inch)	10 AWG Solid - 2 AWG Solid, 8 AWG Stranded - 1 AWG Stranded	

**Two SKUs cover all your termination needs... saves on inventory!**

**Galvan Industries, Inc.**  
www.galvanelectrical.com • 704-455-5102

